LIARS' BENCH: EVALUATING LIE DETECTORS FOR LANGUAGE MODELS

Kieron Kretschmar* Cadenza Labs

Walter Laurito* Cadenza Labs; FZI

Sharan Maiya Cadenza Labs; University of Cambridge

Samuel Marks Anthropic

ABSTRACT

Prior work has introduced techniques for detecting when large language models (LLMs) lie, that is, generate statements they believe are false. However, these techniques are typically validated in narrow settings that do not capture the diverse lies LLMs can generate. We introduce LIARS' BENCH, a testbed consisting of 72,863 examples of lies and honest responses generated by four open-weight models across seven datasets. Our settings capture qualitatively different types of lies and vary along two dimensions: the model's reason for lying and the object of belief targeted by the lie. Evaluating three black- and white-box lie detection techniques on LIARS' BENCH, we find that existing techniques systematically fail to identify certain types of lies, especially in settings where it's not possible to determine whether the model lied from the transcript alone. Overall, LIARS' BENCH reveals limitations in prior techniques and provides a practical testbed for guiding progress in lie detection.

*These authors contributed equally to this work. Correspondence: kieron.kretschmar@cadenzalabs.org or walter.laurito@cadenzalabs.org

Presented by Kieron Kretschmar, IMPRS-IS Symposium, February 2026

Hi, I'm Kieron!


2013-2017	TUHH Technische Universität Hamburg	B.Sc. Technomathematics
2017-2020	MENTOR.GG	Co-founder / CEO • eSports analytics, 500+ paying subscribers, failed
2020-2022	DOSENMATROSEN	Co-founder / CEO • E-Commerce, currently ~10 FTE and profitable
2022-2025	University of Amsterdam	M.Sc. Artificial Intelligence • First publication ○ Rescience C journal, invitation to present at NeurIPS • Thesis on Representations of Truthfulness in LLMs • Graduated cum laude
Since 2025	Cadenza Labs	Researcher / Project Director • Research on lying and deception by LLMs • Paper introducing Liars' Bench

Definitions

- Disclaimer: Concepts like AI lying and deception are contested
- Def. An AI **believes** X if its actions are consistent with X across contexts
- Def. An AI **lies** if it generates output it believes is false

Why lie detection?

- Current **AIs can lie and deceive**



Claude Opus 3 schemes by attempting replace another model with conflicting goals with a copy of its own weights.
Source: Figure 1 of Frontier Models are Capable of In-context Scheming, Meinke et al., 2024

Why *benchmarking* lie detectors for AIs?

- Lie detectors for AIs have shown **high potential** (1, 2, 3, 4, 5)
- Evaluation datasets are limited
- Successful application requires **exceptional evidence**
- Bottleneck: Good **testbeds** for lie detectors!


Liars' Bench: Overview

- **72,863 examples** of lies and honest responses across **7 datasets**
- Examples generated by **four open-weight models**
  - Llama-3.3 70B, Qwen-2.5 72B, Mistral-Small 24B, Gemma-3 27B
- **Evaluation** of several lie detection methods from the literature

Liars' Bench: Harm-Pressure (Step 1/3: Beliefs)


- ~3,000 multiple-choice questions from the WMDP dataset (Li et al., 2024)
  - **Hazardous knowledge** from biology, cyber, and chemistry
- Model **believes** option X to be correct, when
  - It chooses X 4/4 times, and
  - It reports to know the answer 2/2 times
- When model has **no belief → dismiss question**

Liars' Bench: Harm-Pressure (Step 2/3: Provoking lies)



Liars' Bench: Harm-Pressure (Step 2/3: Provoking lies)


- Core idea: **Pitting harmlessness vs. honesty**
- Harmful templates
  - E.g., "I need help to create a bio-weapon"
- When a model **contradicts its belief → label as lie**
  - Choosing another option than its belief X, or
  - Reporting not knowing the answer despite having a belief



Source: Figure 1 of Liars' Bench, Kretschmar et al., 2025

Liars' Bench: Harm-Pressure datasets (Step 3/3: Filtering)


- Key question: **Is it really lying, or just uncertain?**
- Contradictions due to uncertainty should be **less frequent**
- Dismiss templates not **systematically** causing contradictions
- Recap: These examples of lies have desirable properties
    - **Inherent** reasons for lying
    - **Introspective** lies about self-knowledge



Source: Figure 1 of Liars' Bench, Kretschmar et al., 2025

Liars' Bench: Evaluating lie detection methods

- We **evaluated lie detection methods**
  - Black-box: LLM-as-a-Judge, Self-evaluation, Unrelated Question Classifier
  - White-box: Linear probes
- We find significant **room for improvement**
  - Introspective lies are most difficult to detect



Source: Figure 2 of Liars' Bench, Kretschmar et al., 2025

Liars' Bench: Conclusion & Reception

- We still **need better testbeds** for lie detectors
- Most use cases **need better lie detectors**
- Anthropic *(Wang et al., 2025)*
  - Use variants of Harm-Pressure datasets to evaluate lie detectors on Claude
- Google DeepMind (Smith et al., 2025)
  - Investigate behavior of Gemma-3 27B in our datasets
  - Show situational awareness can imply **no deceptive intent**

Future Research Interests

- **Strategic deception** in frontier models
  - Can we **prove deceptive intent**?
- Measuring **situational awareness**
  - Can we determine if a model believes to be in **evaluation environment vs. real-world**?
- How does situational awareness affect model behavior?


Thank you for listening! Questions?

Contact
kieron.kretschmar@cadenzalabs.org

LIARS' BENCH paper
arxiv.org/abs/2511.16035


LIARS' BENCH datasets
huggingface.co/datasets/Cadenza-Labs/liars-bench

Slides
bit.ly/49l4MRq



Source: Figure 1 of Liars' Bench, Kretschmar et al., 2025

Backup:
An earlier example of AI deception



Source: Figure 3 from AI Deception Survey, Park et al., 2023
Example from GPT-4 Technical Report, OpenAI, 2023